



| NOZZLE | DESCRIPTION | SIZE | QTY | FILTER PERFORMANCE | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES DECIMALS ANGULAR .XX +.05 ±0.5 DEG. .XXX ±.01 | | | | |
|--------|----------------|----------|-----|---------------------------------|------|---|------------------|---------|--------|--|
| N1 | INLET | 16" 150# | 1 | MAX FLOW RATE (gpm) | 4500 | | G16-LP180 | | | |
| N2 | OUTLET | 16" 150# | 1 | SCREEN AREA (ft. ²) | 18 | | | | | |
| N3 | FLUSH OUTLET | 2" FNPT | 1 | MAX TEMP. (°F) | 150 | SIZE | FSCM NO. | DWG NO. | REV | |
| N4 | SERVICE PORT | 4" VIC | 2 | MAX PRES. (psi) | 150 | G16-LP180 0 | | | | |
| N5 | COUPLING | 1" FNPT | 2 | VESSEL WEIGHT (lbs) | 1200 | SCALE | SHEET | | 1 of 1 | |
| K1 | HYD CONNECTION | ¼" FNPT | 2 | | | 3.50 | | | | |
| K2 | HYD CONNECTION | ¼" FNPT | 2 | | | | | | | |
| K3 | HYD CONNECTION | ¼" FNPT | 2 | | | | | | | |